



MAXAM

MS307

PORTXTRA RADIAL PORT IND3

Radial Port tire designed for heavy loads and long cycle times typical of demanding application.

- Heavy duty radial construction for container handling service
- Reinforced sidewall and wide tread profile for improved stability
- Tread patterns designed to reduce heat generation
- Special tread compound specially made for industrial application resistant to cut and wear

Applications:



Size	Rating	Type	Rim	O.D.	S.W.	T.D.	TRA	L.I.	Infl. P.	Speed	Tire Load	
											Load Wheels	Steer Wheels
				mm inch	mm inch	mm inch			kPa psi	km/h mph	kg lbs	kg lbs
12.00R20	***	TT	8.5-20	1140	315	29	IND-3	176 A5	1000	25	9230	7100
				44,9	12,4	37/32			145	15	20410	15700
12.00R24	***	TT	8.5-24	1255	315	29	IND-3	178 A5	1000	25	9750	7500
				49,4	12,4	37/32			145	15	21450	16500
14.00R24	***	TT	10.0-24	1369	378	40	IND-3	193 A5	1000	25	14950	11500
				53,9	14,9	50/32			145	15	33020	25400
14.00R24	***	TL	10.0-24	1369	378	40	IND-3	193 A5	1000	25	14950	11500
				53,9	14,9	50/32			145	15	33020	25400





MAXAM

MS407

PORTXTRA RADIAL PORT IND4

Radial Port tire designed for heavy loads and short cycle times typical of demanding application.

- Heavy duty radial construction for container handling service
- Reinforced sidewall and wide tread profile for improved stability
- Tread patterns with extra tread depth designed to maximize tread life
- Special tread compound specially made for industrial application resistant to cut and wear

Applications:



Size	Rating	Type	Rim	O.D.	S.W.	T.D.	TRA	L.I.	Infl. P.	Speed	Tire Load	
											Load Wheels	Steer Wheels
				mm	mm	mm			kPa	km/h	kg	kg
				inch	inch	inch			psi	mph	lbs	lbs
10.00R20	***	TT	8.5-20	1064 41,9	285 11,2	35 44/32	IND-4	166 A5	1000 145	25 15	6890 15210	5300 11700
12.00R20	***	TT	8.5-20	1140 44,9	300 11,8	40 50/32	IND-4	176 A5	1000 145	25 15	9230 20410	7100 15700
12.00R24	***	TT	8.5-24	1255 49,4	315 12,4	40 50/32	IND-4	178 A5	1000 145	25 15	9750 21450	7500 16500
14.00R24	***	TT	10.0-24	1413 55,6	380 15	60 76/32	IND-4	193 A5	1000 145	25 15	14950 33020	11500 25400
14.00R24	***	TL	10.0-24	1413 55,6	380 15	60 76/32	IND-4	193 A5	1000 145	25 15	14950 33020	11500 25400
18.00R25	***	TL	13.00/2.5-25	1645 64,8	500 19,7	62 78/32	IND-4	207 A5	1000 145	25 15	22750 50180	17500 38600

More sizes in preparation

